



katla natural light

Strength & size.

Designed & made in Norway, Grand Majestic represents the latest evolution in the progressive technology of BerryAlloc® High Pressure Floors. Merging trend shaping aesthetics with high performance, Grand Majestic is the pinnacle of our HPF innovation: the world's strongest laminate floor in a plank of extraordinary dimensions that remains easy to fit and simple to care for.



etna light brown

BERRY  **ALLOC**

Alloc AS
 Fibovien 26
 4580 Lyngdal - Norway
 T +47 38 34 22 00
 info@berryalloc.com

berryalloc.com

grand majestic.

When size matters.

BERRY  **ALLOC**



high pressure floors.

Celebrate the majesty of nature with our extra-long and super-wide planks.

Grand Majestic welcomes the majesty of unique super-wide and extra-long planks for a strong and beautiful floor. With its 2,4 m long and 30 cm wide planks, this brand new collection creates a wonderful feeling of open space.




katla natural

Natural & elegant.

In timeless and elegant wood decors, Grand Majestic captures the calming and soothing force of nature in a floor that can handle everything life can throw at it.



etna dark brown



high pressure
extreme
durable



AluLoc



XXlong



XXwide



water
resistant



lifetime
warranty
residential



SilentSystem



made in Norway



Made to last, made for life.

Durable and water resistant, this irresistible premium-quality floor is ideal for busy spaces.

Collection guide. Pick your color



etna light brown
62001986



etna brown
62001987



etna dark brown
62001988




katla natural
62001990



katla natural light
62001989



katla natural honey
62001991



How to install?

The floor must be able to move in all directions after installation. Therefore, certain guidelines must be followed:

- Do not screw, glue or wedge the floor so it can't move, free flow is important. In gaps, FillerTwine (resilient poly foam) is used to not lock the floor.
- Distance to wall and fixed constructions, regardless of area, is 4 mm.
- Use a skirting with a minimum width of 14 mm. T-profiles must be used in transition to a new room.

Kitchen cabinets, kitchen island and other fixtures should not be installed on top of the floor. The end joints must be staggered min. 1/3 of a floorboard.

When choosing the direction of installing on the floor, you should think of the following:

- The longitudinal direction of the room.
- Light input from windows.
- Longitudinal direction of the roof panel

Technical guide

grand majestic



Dimensions	EN 13329	2410 x 303 mm
Total thickness (incl. underlay)	EN 13329	12,3 mm
Thickness of the wear layer	EN 24340	0,6 mm
Click system		AluLoc
Total weight		22,3 kg
Usage classification	EN 13329	23/34
Integrated underlay		SilentSystem
Underfloor heating		suitable max. 27°C (80°F), electrical heating systems max. 60 W/m ²
Thermal resistance	DIN 52612-3	0,13 m ² K/W
Static electrical propensity	EN 1815	< 2,0 kV (antistatic)
Abrasion resistance	EN 13329	AC 6 (IP > 8500)
Impact resistance	EN 13329	> 2000 mm, > 25 N
Thickness swelling	EN 13329	< 7%
Resistance to staining	EN 438.2.26	5
Formaldehyde	EN 717-1	< 0,03 mg/ m ³ (M1)
Fire resistance	EN 13501-1	Bfl-s1
Castor chair	EN 425	No visible damage
Furniture leg	EN 424	No visible damage
Slip resistance	EN 13893	Class DS
Sound reduction: impact sound	EN 717-2	19 dB
Residential warranty		Lifetime
Commercial warranty		10 year

**Inspiration, tutorials, installation instructions
and much more here:**

